



M00000066
Connector, gasblock, 14/10mm



Description

Maunt supplies a complete range of high quality mini pipe fittings (push-fit) for the FTTx market. The portfolio is used to connect, seal and gas seal mini tubes at cable exit points. In addition, the portfolio is completed with reduction couplings for connecting different pipe diameters. The pipe couplings are available for underground and overhead applications.

The gas-block couplings push-fit from the Maunt range connect, among other things, mini tubes with the same diameter. The couplings are used in the construction of FttX networks in places where the cable comes out of a mini-tube and it must be sealed gas- and watertight. Sealing is done by hand-tightening the yellow ring.

Brand

Maunt



Product specifications

Plastic housing	Polycarbonate
O-ring	NBR
Plastic ring	POM
Grip spring washer	Stainless steel (type SUS)
Block clip	POM
Pressure ring	POM
Housing colour	Transparent
Tube diameter	14/10mm
Type of tube	HDPE
Attachment	Push-Fit

Mechanical specifications

Maximum pressure	16 bar
Number of connections	10

Environmental specifications

Transport and storage temperature	-10 to +50°C
Installation temperature	-10 to +50°C
Ambient temperature	-30 to +60°C
Recommended blowing temperature	-5 to +35°C
Outdoor exposure limit	12 months
Test for water ingress	No water leakage (0.5 bar for 168 hours)
Tube mounting	No tools required

Other specifications

Tested according to EN-50411-2-8	Connector is not resistant to turpentine
----------------------------------	--